

MODEL	TRANSMISSION*			ENGINE								PTO					
	4-speed Powershift with Powershuttle		Speed* Continuously Variable Transmission	Max. engine power ECE R120 ¹⁾ Power Plus ²⁾ [kW/hp]	Max. engine power ECE R120 ¹⁾ [kW/hp]	Engine speed at max. engine power [rpm]	Max. torque with Power Plus ²⁾ [Nm @ 1.500 rpm]	Max. torque [Nm @ 1.500 rpm]	Torque rise OECD Standard/Power Plus ²⁾ [%]	Common Rail, 4-valve diesel engine, turbocharger and intercooler / Stage IV	Fuel tank capacity	Electro-hydraulic engagement with soft start					
	16 forward- and reverse-speeds	17 forward- and 16 reverse-speeds 40 km/h Economy										PTO speed [rpm]	at engine speed [rpm]		Ground speed PTO	Front PTO* [rpm]	
32 forward- and reverse-speeds with creeper	17 forward- and 16 reverse-speeds 50 km/h	0 – 50 km/h or 0 – 40 km/h ECO	Rated engine power ECE R120 ¹⁾ Power Plus ²⁾ [kW/hp]	Rated engine power ECE R120 ¹⁾ [kW/hp]	Rated engine speed [rpm]	540/540E/1000	540E/1000/1000E	1,969/1,546/1,893	1,592/1,893/1,621	1,000 @ 1,895 rpm							
4115 PROFI CLASSIC	■	□	-	107 / 145 96 / 131	92 / 125 85 / 116	1,800 – 1,900 2,200	590	528	41 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4125 PROFI CLASSIC	■	□	-	114 / 155 103 / 140	99 / 135 92 / 125	1,800 – 1,900 2,200	637	560	40 / 43	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4135 PROFI CLASSIC	■	□	-	124 / 169 114 / 155	107 / 145 99 / 135	1,800 – 1,900 2,200	700	605	40 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4145 PROFI CLASSIC	■	□	-	129 / 175 118 / 160	114 / 155 107 / 145	1,800 – 1,900 2,200	700	650	40 / 37	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
6145 PROFI CLASSIC	■	□	-	129 / 175 121 / 165	116 / 158 107 / 145	1,800 – 1,900 2,200	740	650	40 / 40	6 / 6,728	198 (230) / 39.5	□	■	□	■	□	□
4115 PROFI	■	□	-	107 / 145 96 / 131	92 / 125 85 / 116	1,800 – 1,900 2,200	590	528	41 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4125 PROFI	■	□	-	114 / 155 103 / 140	99 / 135 92 / 125	1,800 – 1,900 2,200	637	560	40 / 43	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4135 PROFI	■	□	-	124 / 169 114 / 155	107 / 145 99 / 135	1,800 – 1,900 2,200	875	770	40 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4145 PROFI	■	□	-	129 / 175 118 / 160	114 / 155 107 / 145	1,800 – 1,900 2,200	940	770	40 / 37	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
6145 PROFI	■	□	-	129 / 175 121 / 165	116 / 158 107 / 145	1,800 – 1,900 2,200	940	840	40 / 40	6 / 6,728	198 (230) / 39.5	□	■	□	■	□	□
4115 PROFI CVT	-	-	■	107 / 145 96 / 131	92 / 125 85 / 116	1,800 – 1,900 2,200	590	528	41 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4125 PROFI CVT	-	-	■	114 / 155 103 / 140	99 / 135 92 / 125	1,800 – 1,900 2,200	637	560	40 / 43	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4135 PROFI CVT	-	-	■	124 / 169 114 / 155	107 / 145 99 / 135	1,800 – 1,900 2,200	700	605	40 / 42	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□
4145 PROFI CVT	-	-	■	129 / 175 118 / 160	114 / 155 107 / 145	1,800 – 1,900 2,200	700	650	40 / 37	4 / 4,485	198 (230) / 39.5	■	□	■	□	□	□

MODEL	HYDRAULIC										4WD	FRONT AXLE/STEERING			BRAKES	TYRES	WEIGHT	CAB					
	Electr. Hitch regulation EHR with dynamic Ride Control	Max. pump flow				Max. lift capacity 80 / 113 / 125 l/min pump [kg]	Remote valves					integrated front hitch* max. lift capacity 80 / 113 / 125 l/min pump [kg]	Engagement electro hydraulic with Traction-Management	Suspended front axle					Steering system/steering wheel Hydraulic / height- and tilt adjustable	steering lock angle [°]	Wet Dual disk brakes, hydraulically operated 4-wheel brake* with Opti-Stop Two-line-air-trailer brake*	Max. tyres ⁴⁾ front	Min. weight [kg]* / permissible total weight* [kg]
		80 l/min with OCLS pump	113 l/min with CCLS pump load sensing	125 l/min with CCLS pump, load sensing	rear, up to 4 free configurable, 1 Power Beyond-connection		mid mount																
					mechanical	electrical	up to 2 mechanical	up to 2 electrical															
4115 PROFI CLASSIC	■	■	□	-	7,115 / 7,864 / -	■	-	■	-	2,800 / 3,100 / -	■	□	■	44° 4.6	■	440/65 R28 540/65 R38	4,890 9,500	Comfort-Low roof cab* Suspended comfort-low roof cab with air condition and noise level inside cab 73 dB(A). fabric driver seat with air suspension, comfortable passenger seat with safety belt. Tinted glass, opening rear window, roof window, wash/wipe system, front and rear, LED work lights on cab roof front and rear, control panel for work lights. Optional with standard roof.					
4125 PROFI CLASSIC	■	■	□	-	7,115 / 7,864 / -	■	-	■	-	2,800 / 3,100 / -	■	□	■	44° 4.6	■	440/65 R28 540/65 R38	4,890 9,500						
4135 PROFI CLASSIC	■	■	□	-	7,115 / 7,864 / -	■	-	■	-	2,800 / 3,100 / -	■	□	■	44° 4.6	■	440/65 R28 540/65 R38	4,890 9,500						
4145 PROFI CLASSIC	■	■	□	-	7,115 / 7,864 / -	■	-	■	-	2,800 / 3,100 / -	■	□	■	44° 4.6	■	440/65 R28 540/65 R38	5,010 9,500						
6145 PROFI CLASSIC	■	■	□	-	7,115 / 7,864 / -	■	-	■	-	2,800 / 3,100 / -	■	□	■	44° 4.6	■	440/65 R28 540/65 R38	5,020 9,500						
4115 PROFI	■	-	■	-	- / 7,864 / -	-	■	-	■	- / 3,100 / -	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500	Comfort-Cab* Suspended comfort cab with air condition and noise level inside cab 69 dB(A). Dual-Motion-driver seat with fabric, comfortable passenger seat with safety belt. Multicontroller-armrest with ICP (Intuitive Control Panel) and Joystick. S-TECH 700 Monitor with ISOBUS II-connection. Tinted glass, opening rear window, roof window, wash/wipe system, front and rear, LED work lights on cab roof front and rear, control panel for work lights. Optional with low roof					
4125 PROFI	■	-	■	-	- / 7,864 / -	-	■	-	■	- / 3,100 / -	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500						
4135 PROFI	■	-	■	-	- / 7,864 / -	-	■	-	■	- / 3,100 / -	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500						
4145 PROFI	■	-	■	-	- / 7,864 / -	-	■	-	■	- / 3,100 / -	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	5,010 9,500						
6145 PROFI	■	-	■	-	- / 7,864 / -	-	■	-	■	- / 3,100 / -	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	5,020 9,500						
4115 PROFI CVT	■	-	-	■	- / - / 7,864	-	■	-	■	- / - / 3,100	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500	Deluxe-Cab* Like Comfort-Cab and in addition: automatic climate control, electr. adjustment of Multicontroller-armrest, sun shade at rear window and carpet.					
4125 PROFI CVT	■	-	-	■	- / - / 7,864	-	■	-	■	- / - / 3,100	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500						
4135 PROFI CVT	■	-	-	■	- / - / 7,864	-	■	-	■	- / - / 3,100	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	4,890 9,500						
4145 PROFI CVT	■	-	-	■	- / - / 7,864	-	■	-	■	- / - / 3,100	■	□	■	44° 4.6	■	480/65 R28 600/65 R38	5,010 9,500						

■ Standard □ Optional - Not available

* Depending on country-specific legislation and specifications ¹⁾ ECE R120 correspond to ISO 14396 and 97/68EG ²⁾ Power Plus is enabled if certain conditions apply during transport, hydraulic and PTO work. ³⁾ with standard tyres ⁴⁾ Other tyres available on request